

TMRW15L Torque Motor



Electrical specifications

Winding code : PA	Symbol	Unit	Free air convection	Water cooling
Continuous torque	T_c	Nm	12.4	31.3
Continuous current	I_c	A_{rms}	5.7	14.4
Stall torque	T_s	Nm	9	22
Stall current	I_s	A_{rms}	4	10.1
Peak torque(for 1sec.)	T_p	Nm	36.2	59.4
Peak current(for 1sec.)	I_p	A_{rms}	17.1	38.9
Torque constant	K_t	Nm/Arms	2.18	
Electrical time constant	T_e	ms	3.4	
Resistance (line to line at 25°C)	R_{25}	Ω	2.36	
Inductance (line to line)	L	mH	8	
Number of poles	2p		22	
Back emf constant (line to line)	K_v	Vrms/rad/s	1.26	
Motor constant (at 25°C)	K_m	Nm/ \sqrt{W}	1.16	
Thermal resistance	R_{th}	K/W	0.83	0.129
Thermal sensor			PTC SNM100+SNM120+Pt1000	
Max. DC BUS		V_{DC}	750	
Inertia of rotor	J	kgm^2	0.0016	
Thermal time constant	T_{th}	s	2720	98
Max. continuous power dissipation	P_c	W	157	1007
Max. peak power dissipation	P_p	W	7354	
Rated speed(at 600VDC)		rpm	820	


Mechanical specifications

	Symbol	Unit	Free air convection	Water cooling
Mass of rotor	M_r	kg	1	
Mass of stator	M_s	kg	5.1	
Height of stator	H_s	mm	90	
Height of rotor	H_r	mm	51	
Length of rotor centring fit	H	mm	15	
Water temperature difference for P_c	$\Delta\theta$	K	-	5
Minimum water flow	q	l/min	-	2.9
Max. pressure drop	Δp	bar	-	1

T-N curve



Thermal sensor



Except dimensions, all the specifications in the table are in $\pm 10\%$ of tolerance

Version: 2.00

This drawing is only for reference, detail dimensions please refer to approval drawing.

Date: 2020/10/23