

TMRWDAL Torque Motor



Electrical specifications

Winding code : SD	Symbol	Unit	Free air convection	Water cooling
Continuous torque	T_c	Nm	619	1340
Continuous current	I_c	A_{rms}	24	60
Stall torque	T_s	Nm	433	938
Stall current	I_s	A_{rms}	16.8	42
Peak torque(for 1sec.)	T_p	Nm	1543	2470
Peak current(for 1sec.)	I_p	A_{rms}	72	162
Torque constant	K_t	Nm/Arms	25.8	
Electrical time constant	T_e	ms	7	
Resistance (line to line at 25°C)	R_{25}	Ω	1.04	
Inductance (line to line)	L	mH	7.33	
Number of poles	2p		88	
Back emf constant (line to line)	K_v	Vrms/rad/s	14.9	
Motor constant (at 25°C)	K_m	Nm/ \sqrt{W}	20.65	
Thermal resistance	R_{th}	K/W	0.11	0.017
Thermal sensor			PTC SNM100+SNM120+Pt1000	
Max. DC BUS		V_{DC}	750	
Inertia of rotor	J	kgm^2	0.53	
Thermal time constant	T_{th}	s	3840	110
Max. continuous power dissipation	P_c	W	1235	7722
Max. peak power dissipation	P_p	W	56293	
Rated speed(at 600VDC)		rpm	190	



Mechanical specifications

	Symbol	Unit	Free air convection	Water cooling
Mass of rotor	M_r	kg	18.3	
Mass of stator	M_s	kg	76	
Height of stator	H_s	mm	160	
Height of rotor	H_r	mm	101	
Length of rotor centring fit	H	mm	15	
Water temperature difference for P_c	$\Delta\theta$	K	-	5
Minimum water flow	q	l/min	-	22.1
Max. pressure drop	Δp	bar	-	1

T-N curve



Thermal sensor



General tolerance mm	
Nominal dimension	Tolerance
~ 6	±0.1
> 6 ~ 30	±0.2
> 30 ~ 120	±0.3
> 120 ~ 300	±0.4
> 300 ~ 600	±0.5
> 600 ~ 1200	±0.8
> 1200 ~ 2400	±1.0
> 2400	±1.5

Motor wire table	
Color or wire no.	Signal
U/L1	PH U
V/L2	PH V
W/L3	PH W
Green/Yellow	GND

Except dimensions, all the specifications in the table are in ±10% of tolerance

Version: 2.00

This drawing is only for reference, detail dimensions please refer to approval drawing.

Date: 2020/10/23