

TMRW27L Torque Motor



Electrical specifications

Winding code : SA	Symbol	Unit	Free air convection	Water cooling
Continuous torque	T_c	Nm	33	82.5
Continuous current	I_c	A_{rms}	4.9	12.3
Stall torque	T_s	Nm	23	58
Stall current	I_s	A_{rms}	3.4	8.6
Peak torque(for 1sec.)	T_p	Nm	95.9	156
Peak current(for 1sec.)	I_p	A_{rms}	14.7	33.2
Torque constant	K_t	Nm/Arms	6.72	
Electrical time constant	T_e	ms	6.5	
Resistance (line to line at 25°C)	R_{25}	Ω	3.5	
Inductance (line to line)	L	mH	22.72	
Number of poles	2p		22	
Back emf constant (line to line)	K_v	Vrms/rad/s	3.88	
Motor constant (at 25°C)	K_m	Nm/ \sqrt{W}	2.94	
Thermal resistance	R_{th}	K/W	0.75	0.12
Thermal sensor			PTC SNM100+SNM120+Pt1000	
Max. DC BUS		V_{DC}	750	
Inertia of rotor	J	kgm^2	0.0063	
Thermal time constant	T_{th}	s	2680	120
Max. continuous power dissipation	P_c	W	172	1089
Max. peak power dissipation	P_p	W	7936	
Rated speed(at 600VDC)		rpm	800	


Mechanical specifications

	Symbol	Unit	Free air convection	Water cooling
Mass of rotor	M_r	kg	2.2	
Mass of stator	M_s	kg	10.2	
Height of stator	H_s	mm	120	
Height of rotor	H_r	mm	71	
Length of rotor centring fit	H	mm	15	
Water temperature difference for P_c	$\Delta\theta$	K	-	5
Minimum water flow	q	l/min	-	3.2
Max. pressure drop	Δp	bar	-	1

T-N curve



Thermal sensor



Except dimensions, all the specifications in the table are in ±10% of tolerance

Version: 2.00

This drawing is only for reference, detail dimensions please refer to approval drawing.

Date: 2020/10/23